2015/830 - Europe

Date of issue/ Date of : 2/17/2021 Date of previous issue : 11/27/2020 revision



SAFETY DATA SHEET

VALTTI PLUS WOOD OIL

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : VALTTI PLUS WOOD OIL
Product description : Wood oil, waterborne

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Painting work

1.3 Details of the supplier of the safety data sheet

Manufacturer or Distributor

Tikkurila Oyj P.O. Box 53 FI-01301 VANTAA

FINLAND

Telephone +358 20 191 2000

e-mail address of person : Tikkurila Oyj, responsible for this SDS : Product Safety,

e-mail: productsafety@tikkurila.com

1.4 Emergency telephone number

Telephone number : 112 (24h)

Supplier or Manufacturer

Telephone number : Tikkurila Oyj

+358 20 191 2000 (GMT +2) Mon-Fri 8-16

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

2.2 Label elements

Signal word : No signal word.

Hazard statements : H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements

General : Not applicable.

Prevention: P273 - Avoid release to the environment.

Response : Not applicable.

Storage : Not applicable.

Disposal : Not applicable.

Version : 2

Date of issue/Date of revision 17.02.2021 Date of previous issue 27.11.2020. VALTTI PLUS WOOD OIL

Supplemental label elements

: Contains 3-iodo-2-propynyl butylcarbamate (IPBC) and reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (C(M)IT/MIT (3:1)). May produce an allergic reaction.

Treated articles

This product contains a biocidal product for the preservation of the product during storage. Contains C(M)IT/MIT (3:1). Wear protective gloves.

2.3 Other hazards

Other hazards which do not result in classification

: **Note!** Risk of self-ignition of used cleaning rags, paper wipes etc. Contaminated materials can create fire some hours later and should be soked in water and placed in a closed metal container before disposal.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

			<u>Classification</u>	
Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Notes
3-iodo-2-propynyl butylcarbamate (IPBC)	REACH #: 01-2120762115-60 EC: 259-627-5 CAS: 55406-53-6	<1	Acute Tox. 4, H302 Acute Tox. 3, H331 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 1, H372 (larynx) Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=1)	-
Dodecan-1-ol, ethoxylated	EC: 500-002-6 CAS: 9002-92-0	≤0.3	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=1)	-
bronopol	REACH #: 01-2119980938-15 EC: 200-143-0 CAS: 52-51-7 Index: 603-085-00-8	≤0.061	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 1, H400 (M=10)	-
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (C(M)IT/MIT (3:1))	CAS: 55965-84-9 Index: 613-167-00-5	<0.001	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100) EUH071 See Section 16 for the full text of the H statements declared above.	-

There are no additional ingredients present which, within the current knowledge of the supplier, are classified and contribute to the classification of the substance and hence require reporting in this section.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Notes, if applicable, refer to Notes given in Annex VI of 1272/2008/EC.

SECTION 4: First aid measures

4.1 Description of first aid measures

General : In all cases of doubt, or when symptoms persist, seek medical attention. Show this

safety data sheet or label to the doctor if possible.

Eye contact: Check for and remove any contact lenses. Immediately flush eyes with plenty of

lukewarm water, keeping eyelids open. Continue to rinse for at least 15 minutes.

Inhalation: Remove to fresh air.

Version : 2 2/9

Date of issue/Date of revision	17.02.2021 Date of previous issue	27.11.2020.	VALTTI PLUS WOOD OIL	

Skin contact : Wash skin thoroughly with soap and water or use recognized skin cleanser. Do

NOT use solvents or thinners.

Ingestion : If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious). If significant amounts have been swallowed or if symptoms persist,

seek medical attention.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Contains:

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (C(M)IT/MIT (3:1))

3-iodo-2-propynyl butylcarbamate (IPBC)

May produce an allergic reaction.

4.3 Indication of any immediate medical attention and special treatment needed

None.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire. Recommended: Alcohol resistant foam, CO₂, powders or water spray/mist.

Unsuitable extinguishing media

: Do not use a direct water jet that could spread the fire.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

: This product is not classified as flammable. Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

Hazardous combustion products

: When exposed to high temperatures, hazardous decomposition products may be produced, such as carbon monoxide and dioxide, smoke, oxides of nitrogen etc.

5.3 Advice for firefighters

Special protective actions for fire-fighters

: Use water spray to keep fire-exposed containers cool. This material is hazardous to aquatic organisms. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Special protective equipment for fire-fighters

: Appropriate breathing apparatus may be required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

: Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

: Hazardous to aquatic environment. Do not allow to enter drains, water courses or soil.

6.3 Methods and materials for containment and cleaning up

: Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Preferably clean with water or detergent. Avoid using solvents.

6.4 Reference to other sections

: See Section 1 for emergency contact information. See Section 13 for additional waste treatment information.

Version : 2 3/9

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid breathing vapor. Avoid inhalation of dust from sanding. See Section 8 for information on appropriate personal protective equipment. Eating, drinking and smoking should be prohibited in areas where this material is handled and stored. Wash hands before breaks and immediately after handling the product. Avoid release to the environment.

Risk of self-ignition! Materials such as cleaning rags and paper wipes, sanding dust and overspray containing the product, may spontaneously self-ignite some hours later. To avoid the risks of fires, all contaminated materials should be placed in a metal container filled with water and sealed or dried preferably outdoors or incinerated immediately. Contaminated materials should be removed from the workplace at the end of each working day and be stored outside.

7.2 Conditions for safe storage, including any incompatibilities

Store in original container protected from direct sunlight in a dry, cool and wellventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Recommended storage temperature is +5°C ...+25°C. Do not allow to freeze. Store in accordance with local regulations.

7.3 Specific end use(s)

: None.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits No exposure limit value known.

procedures

Recommended monitoring: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

DNELs/DMELs

No DNELs/DMELs available.

PNECs

No PNECs available.

8.2 Exposure controls

Appropriate engineering controls

Provide adequate ventilation. Comply with the health and safety at work laws.

Individual protection measures

Eye/face protection

: Safety eyewear should be used when there is a likelihood of exposure.

Hand protection

: Wear protective gloves. Gloves should be replaced regularly and if there is any sign of damage to the glove material. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Recommended glove material (EN374): > 8 hours (breakthrough time): nitrile rubber

Not recommended: PVA gloves

Skin protection

: Wear appropriate personal protective clothing to prevent skin contact.

Respiratory protection

: A respirator is not needed under normal and intended conditions of product use. Wear a respirator with type P2 filter during sanding (EN149:2001). Be sure to use an approved/certified respirator or equivalent. Check that mask fits tightly and

change filter regularly.

Environmental exposure controls

: For information regarding environmental protection measures, please refer to section 13 for waste handling, section 7 for handling and storage and section 1.2 for relevant identified uses of the substance or mixture and uses advised against.

Version : 2 4/9

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid. Color : Various Odor : Mild.

: Not relevant for the hazard assessment of the product. **Odor threshold** Hq : Not relevant for the hazard assessment of the product.

Melting point/freezing point : 0°C (water) Initial boiling point and

boiling range

100°C (water)

Flash point : > 100 °C

Evaporation rate : Not relevant due to the nature of the product.

Flammability (solid, gas) : Not applicable. Product is a liquid. Upper/lower flammability or : No flammable ingredients present.

explosive limits

Vapor pressure : 3.2 kPa [room temperature] (water)

Vapor density : Not relevant for the hazard assessment of the product.

Density 1 g/cm³

Solubility(ies) : Miscible in water. Partition coefficient: n-octanol/: Not available.

water

Auto-ignition temperature : Not relevant due to the nature of the product.

Decomposition temperature : Not relevant for the hazard assessment of the product. : Not relevant for the hazard assessment of the product. **Viscosity**

Explosive properties : No explosive ingredients present. Oxidizing properties : No oxidizing ingredients present.

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

: See Section 10.5. 10.1 Reactivity

10.2 Chemical stability : Stable under recommended storage and handling conditions (see Section 7).

10.3 Possibility of : Under normal conditions of storage and use, hazardous reactions will not occur. hazardous reactions

10.4 Conditions to avoid : Avoid extreme heat and freezing.

10.5 Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions:

> oxidizing agents strong acids strong alkalis

10.6 Hazardous : When exposed to high temperatures, hazardous decomposition products may be decomposition products produced, such as carbon monoxide and dioxide, smoke, oxides of nitrogen etc.

5/9 Version : 2

SECTION 11: Toxicological information

11.1 Information on toxicological effects

There is no testdata available on the product itself.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Long term exposure by inhalation may cause respiratory tract irritation. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Acute toxicity

Not classified.

Irritation/Corrosion

Not classified.

Sensitization

Not classified.

The product contains sensitizing substances mentioned in sections 2 and 3.

Mutagenicity

Not classified.

Carcinogenicity

Not classified.

Reproductive toxicity

Not classified.

Teratogenicity

Not classified.

Specific target organ toxicity (single exposure)

Not classified.

Specific target organ toxicity (repeated exposure)

Not classified.

Aspiration hazard

Not classified.

SECTION 12: Ecological information

Ecological testing has not been conducted on this product.

Do not allow to enter drains, water courses or soil.

The product is classified as environmetally hazardous according to Regulation (EC) 1272/2008. Harmful to aquatic life with long lasting effects.

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
3-iodo-2-propynyl butylcarbamate (IPBC)	EC50 0.053 mg/l	Algae 72 ho	
	EC50 0.16 mg/l	Daphnia	48 hours
	LC50 0.067 mg/l	Fish	96 hours
	NOEC 0.05 mg/l	Daphnia - Daphnia magna	21 days
bronopol	Acute EC50 0.068 mg/l	Algae - Anabaena flos aqua	72 hours

12.2 Persistence and degradability

Version : 2 6/9

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
eaction mass of 5-chloro- -methyl-2H-isothiazol- -one and 2-methyl-2H- sothiazol-3-one (3:1) (C(M) T/MIT (3:1))	-	-	Readily

27.11.2020.

17.02.2021 Date of previous issue

VALTTI PLUS WOOD OIL

12.3 Bioaccumulative potential

Date of issue/Date of revision

Product/ingredient name	LogP _{ow}	Bioconcentration factor [BCF]	Potential
bronopol	0.18	-	low

12.4 Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects : Not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal

: Remove as much product as possible from the tools before cleaning. Liquid residue and cleaning liquids are hazardous waste and must not be emptied into drains or sewage system, but handled in accordance with national regulations. Product residues should be left at special companies which have permission for gathering this kind of wastes.

European waste catalogue (EWC)

Waste code	Waste designation	
9 8 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

Packaging

Methods of disposal : Empty packaging should be recycled or disposed of in accordance with national regulations.

Special precautions

: **Risk of self-ignition!** Materials such as cleaning rags and paper wipes, sanding dust and overspray containing the product, may spontaneously self-ignite some hours later. To avoid the risks of fires, waste like this should be placed in a metal container filled with water and sealed before disposal, or dried preferably outdoors or incinerated immediately.

SECTION 14: Transport information

This product is not regulated for carriage according to ADR/RID, IMDG, IATA.

Version : 2 7/9

	ADR/RID	IMDG	IATA
14.1 UN number	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-
14.3 Transport hazard class(es)	-	-	-
14.4 Packing group	-	-	-
14.5 Environmental hazards	No.	No.	No.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments

: Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Other EU regulations

: Not determined. **Europe inventory**

15.2 Chemical Safety **Assessment**

: This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and

acronyms

: ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration

RRN = REACH Registration Number

vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS] Classification **Justification**

Aquatic Chronic 3, H412 Calculation method

Version : 2 8/9

Date of issue/Date of revision	17.02.2021 Date of previous is:	sue 27.11.2020. VALTTI PLUS WOOD OIL
Full text of abbreviated H statements	H318 Causes serious ey H315 Causes skin irritat H317 May cause an alle H335 May cause respira H372 Causes damage to H400 Very toxic to aqua H410 Very toxic to aqua	red. th skin. t with skin. in burns and eye damage. ye damage. ion. ergic skin reaction. atory irritation. o organs through prolonged or repeated exposure. tic life. tic life with long lasting effects. c life with long lasting effects.
Full text of classifications [CLP/GHS]	Acute Tox. 3 Acute Tox. 4 Aquatic Acute 1 Aquatic Chronic 1 Aquatic Chronic 3 Eye Dam. 1 Skin Corr. 1C Skin Irrit. 2 Skin Sens. 1 Skin Sens. 1A STOT RE 1 E STOT SE 3	ACUTE TOXICITY - Category 2 ACUTE TOXICITY - Category 3 ACUTE TOXICITY - Category 4 AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 3 BERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 BKIN CORROSION/IRRITATION - Category 1C BKIN CORROSION/IRRITATION - Category 2 BKIN SENSITIZATION - Category 1 BKIN SENSITIZATION - Category 1 BY SEPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1 BY SEPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 3
Date of issue/ Date of revision	: 2/17/2021	
Date of previous issue	: 11/27/2020	
Versien	. 2	

Version : 2

Notice to reader

This Safety Data Sheet is prepared in accordance with Annex II (EU) No 830/2015 to Regulation (EC) No 1907/2006 (REACH). The information contained in this Safety Data Sheet is based on the present state of knowledge and current EU and national legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

Version : 2 9/9