



## **Tile Splashback:** Step-by-step painting guide.

---

*The surface **must** be free from all traces of oil, grease and dirt. Failure to remove contaminants, even at a microscopic level, could negatively affect the performance and the appearance of the paint.*

---

### **Step 1: Cleaning the Tiles**

Before painting, thoroughly clean the tiles using Seinapesu to remove grease, dirt, and any contaminants that could affect adhesion. Scrub the entire surface with a rough pad, paying extra attention to grout lines, cracks and corners. Once cleaned, rinse away any residue and allow the surface to dry for at least 24 hours. Even if the tiles appear dry, moisture may still be present in the grout lines or cracks, which can impact the final finish.

### **Step 2: Painting the Tiles**

When applying the paint, use a microfiber roller to create a thin, even layer across both the tiles and grout. Avoid using too much paint, as this can cause sagging or an uneven finish. Allow the first coat to dry for at least 16 hours before applying a second coat. Once dry, repeat the same process to ensure smooth, even coverage.

### **Step 3: Maintenance & Care**

After painting, the surface will reach full durability in one month, so handle with care during the first few weeks. If cleaning is necessary during this period, gently wipe the tiles with a damp cloth or soft sponge—avoid scrubbing or using harsh chemicals. Note: Freshly painted surfaces may soften slightly when exposed to water but will harden again after approximately 30 minutes of drying.